

# MATERIALS & SPECIFICATIONS

PART NO.	A79111-001	REV	ECO	DATE	APP
		E	102825	08-19-16	TLM





INSULATOR MATERIAL:  
THERMOPLASTIC POLYMER PER MIL-DTL-32139

CONTACT MATERIAL:  
COPPER ALLOY PER MIL-DTL-32139. GOLD PLATED PER ASTM B488, (HARD GOLD) TYPE II CODE C CLASS 1.27

TERMINATION:  
GOLD PLATED PER ASTM B488, (HARD GOLD) TYPE II CODE C CLASS 1.27

CURRENT CAPACITY:  
1 AMP MAX PER MIL-DTL-32139

CONTACT RESISTANCE:  
71 MILLIOHMS (71 mV) MAX @ 1.0 AMPS PER MIL-DTL-32139



**RoHS**

MCTS	SCN	THIRD ANGLE	THIS DRAWING CONTAINS CONFIDENTIAL AND PROPRIETARY INFORMATION WHICH IS THE PROPERTY OF OMNETICS CONNECTOR CORP. THIS DOCUMENT MAY NOT, IN WHOLE OR IN PART, BE DUPLICATED, OR DISCLOSED FOR ANY PURPOSE, WITHOUT WRITTEN PERMISSION FROM OMNETICS CONNECTOR CORP.	<b>OMNETICS</b> CONNECTOR CORPORATION 7260 COMMERCE CIRCLE EAST MINNEAPOLIS, MN 55432 WWW.OMNETICS.COM	CAGE CODE <b>61873</b>
		-TOLERANCES- UNLESS OTHERWISE NOTED DIMENSIONS IN INCHES			DWTM. ACM
		2 PL DEC ± .01 3 PL DEC ± .005 4 PL DEC ± .0005 ANGLES ± 1°	CHK'D.		SHEET 1 OF 1
			APP'D.		REV E
					SCALE: 4:1