

## ORDERING GUIDE



<b>1 Series</b>	<b>MDLP</b> Low Profile Micro-D Pin	<b>MDLS</b> Low Profile Micro-D Socket
<b>2 Number of Contacts</b>	<b>009</b> <b>015</b> <b>021</b> <b>025</b> <b>031</b>	<b>037</b>
<b>3 Termination Type</b>	<b>WD</b> Discrete Leadwire	
<b>4 Wire AWG</b>	<b>4</b> 24 AWG	<b>6</b> 26 AWG (STD) <b>8</b> 28 AWG <b>0</b> 30 AWG
<b>5 Wire Type</b>	<b>Q</b> Nema HP3 (STD)	<b>R</b> M22759/11 <b>S</b> M22759/33 <b>X</b> Other
<b>6 Wire Length (inches)</b>	<b>18.0</b> 18.00 (STD)	<b>XX.X</b> Custom length
<b>7 Color Scheme</b>	<b>1</b> 10 Repeating <b>2</b> Blue <b>3</b> White	<b>4</b> Non Repeating <b>5</b> Yellow
<b>8 Shell Material &amp; Finish</b>	<b>N</b> Aluminum Shell, Electroless Nickel Plated <b>B</b> Aluminium Shell, Black Anodized	<b>CD</b> Aluminium Shell, Cadmium Plated <b>P</b> Stainless Steel Shell, Passivated
<b>9 Hardware</b>	<b>00</b> None, Ø .092 Hole <b>02</b> Jackscrews, STD Length, Hex (MMDP - STD) <b>04</b> Jackscrews, Long Length, Hex <b>06</b> Float Mount, Front Mounted <b>08</b> Non-Removable	<b>01</b> Fixed Jack-posts (MMDS - STD) <b>03</b> Jackscrews, STD Length, Slotted <b>05</b> Jackscrews, Long Length, Slotted <b>07</b> Float Mount, Rear Mounted <b>YY</b> Non Standard Hardware
<b>10 Common Options</b>	<b>PA</b> Panel Mount Rear, O-Ring <b>IBS</b> Integrated Backshell <b>HT</b> High Temp Epoxy	<b>PB</b> Panel Mount, Rear <b>BSY</b> Custom Backshell <b>RH</b> RoHS Compliant
<b>11 Shield / Jacket</b>	<b>D</b> Slip On Metal Braid <b>E</b> Machine Braid <b>F</b> Flexo Braid <b>J</b> Nomex Braid <b>ST</b> Shrink Tube	
<b>12 Mod Codes</b>	<b>M10</b> Keyed <b>M30</b> Ground Spring <b>M50</b> Space Grade Micro-D, SPT1 <b>M53</b> Space Grade Micro-D, SPT2	
<b>13 Special Instructions</b>	<b>YYY</b> Describe anything that is not covered in standard options	