






# METAL MICRO CIRCULAR DISCRETE LEADWIRE/CABLE (TYPE WD/WC)

Series	# of Contacts	Termination Type	Shell Material and Finish	Shell Type	Options, cont.
MMC	5 12 16 27 39	<b>WD: Discrete Lead Wire</b>	<b>Standard</b> <b>N: Nickel Plated Brass</b>	<b>IS: Inline Shell</b> (shell only)	<b>C</b> Color Coded
		<b>WC: Cable</b>	<b>Non-Standard Options</b> <b>BN: Black Nickel Plated Brass</b>	<b>Options</b> <b>SR: Inline Shell w/ Strain Relief</b>	<b>OR</b> O-Ring
Male (P - Pin)					
Female (S - Socket)			<b>P: Passivated Stainless Steel</b>		
		Wire/Cable Length: 18.0=18.0" Standard Option "XX.X" = Custom Length i.e. 23.4" 26 AWG Max	<b>OX: Black Oxide Finished Steel</b>	<b>ST: Inline Shell w/ Shrink Tube</b>	<b>IP68</b> 
					<b>RH</b> RoHS COMPLIANT 
					<b>OM</b> Overmold (Contact Omnetics for Overmold Information & Availability)
					

**EXAMPLE:**  
MMCS-12-WD-10.0-C-IS-N-SR-OR