












Single Row Micro Strip

PRE-WIRED/CABLE (TYPE WD/WC) ORDERING GUIDE


SERIES	# OF CONTACTS	TERMINATION TYPE	WIRE LENGTH	COLOR CODED	COMMON OPTIONS
PS1 PIN CONNECTOR Standard: .075" thick	02 - 48	WD DISCRETE WIRES	18.00 =18.00" STANDARD	C 10 REPEATING COLORS PER MIL-STD 681 	G GUIDE POST/HOLE GS MULTIPLE GUIDE POSTS/HOLES   LE LATCH (END MOUNT) LES MULTIPLE LATCHES (END MOUNT)   LT LATCH (TOP MOUNT) LTS MULTIPLE LATCHES (TOP MOUNT)   M MOUNTING HOLE   HT HIGH TEMP
PS2 PIN CONNECTOR .100" thick		TW TWISTED WIRES	XX.XX CUSTOM LENGTH i.e. 23.4"		
SSB SOCKET CONNECTOR 		WC CABLE	26 AWG Standard/ MAX		




SSB
SOCKET CONNECTOR




EXAMPLES:



PS1/PS2-11-WD-18.00-C-M-GS



SSB-24-WD-18.0-C-LT



SSB-17-WD-18.0-C-M-GS

RoHS
RoHS
COMPLIANT

